



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** SINT 744-G
Other means of identification:
UFI: YDU3-APPN-3009-DV5J
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Industrial paint. For professional users/industrial user only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Roberlo S.A.U.
Ctra. Nacional II, Km. 706,5
17457 Riudellots de la Selva - Gerona - España
Phone: +34 972 478060 (8:00-12:45 / 14:15-17:30 h) (GMT +1:00) - Fax: +34972477394
msds@roberlo.com
- 1.4 Emergency telephone number:** +44 (0)1924 431679 / 112 / +34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning

Hazard statements:
H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure (Oral).
H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements:
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
Substances that contribute to the classification
Xylene; Hydrocarbons, C9, aromatics
UFI: YDU3-APPN-3009-DV5J
- 2.3 Other hazards:**

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | | Concentration |
|---|---|---|------------------------|
| CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX | Xylene⁽¹⁾ Self-classified | | 25 - <50 % |
| | Regulation 1272/2008 | Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | |
| CAS: 100-41-4 EC: 202-849-4 Index: 601-023-00-4 REACH: 01-2119489370-35-XXXX | Ethylbenzene⁽¹⁾ Self-classified | | 5 - <10 % |
| | Regulation 1272/2008 | Acute Tox. 4: H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger | |
| CAS: 64742-95-6 EC: Non-applicable Index: Non-applicable REACH: Non-applicable | Hydrocarbons, C9, aromatics⁽¹⁾ Self-classified | | 2,5 - <5 % |
| | Regulation 1272/2008 | Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger | |
| CAS: 108-88-3 EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51-XXXX | Toluene⁽¹⁾ Self-classified | | 0,3 - <0,5 % |
| | Regulation 1272/2008 | Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger | |
| CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX | Dipropylene Glycol Methyl Ether⁽²⁾ Not classified | | <0,01 % |
| | Regulation 1272/2008 | | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification | Acute toxicity | | Genus |
|---|-----------------|----------------|-------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | LD50 oral | Non-applicable | |
| | LD50 dermal | Non-applicable | |
| | LC50 inhalation | 11 mg/L (ATEi) | |

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

- CONTINUED ON NEXT PAGE -



SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

- CONTINUED ON NEXT PAGE -



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | | Occupational exposure limits | | |
|--|--|------------------------------|---------|-----------------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | | IOELV (8h) | 50 ppm | 221 mg/m ³ |
| | | IOELV (STEL) | 100 ppm | 442 mg/m ³ |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | | IOELV (8h) | 100 ppm | 442 mg/m ³ |
| | | IOELV (STEL) | 200 ppm | 884 mg/m ³ |
| Toluene CAS: 108-88-3 EC: 203-625-9 | | IOELV (8h) | 50 ppm | 192 mg/m ³ |
| | | IOELV (STEL) | 100 ppm | 384 mg/m ³ |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | | IOELV (8h) | 50 ppm | 308 mg/m ³ |
| | | IOELV (STEL) | | |

DNEL (Workers):

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|-----------------------|-----------------------|-----------------------|
| | | Systemic | Local | Systemic | Local |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 212 mg/kg | Non-applicable |
| | Inhalation | 442 mg/m ³ | 442 mg/m ³ | 221 mg/m ³ | 221 mg/m ³ |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 180 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 293 mg/m ³ | 77 mg/m ³ | Non-applicable |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Non-applicable | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 25 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 150 mg/m ³ | Non-applicable |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 384 mg/kg | Non-applicable |
| | Inhalation | 384 mg/m ³ | 384 mg/m ³ | 192 mg/m ³ | 192 mg/m ³ |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 283 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 308 mg/m ³ | Non-applicable |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|-----------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Oral | Non-applicable | Non-applicable | 12,5 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 125 mg/kg | Non-applicable |
| | Inhalation | 260 mg/m ³ | 260 mg/m ³ | 65,3 mg/m ³ | 65,3 mg/m ³ |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Oral | Non-applicable | Non-applicable | 1,6 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 15 mg/m ³ | Non-applicable |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Non-applicable | Oral | Non-applicable | Non-applicable | 11 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 11 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 32 mg/m ³ | Non-applicable |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Oral | Non-applicable | Non-applicable | 8,13 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 226 mg/kg | Non-applicable |
| | Inhalation | 226 mg/m ³ | 226 mg/m ³ | 56,5 mg/m ³ | 56,5 mg/m ³ |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 121 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 37,2 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|---|--------------|----------------|-------------------------|-------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | STP | 6,58 mg/L | Fresh water | 0,327 mg/L |
| | Soil | 2,31 mg/kg | Marine water | 0,327 mg/L |
| | Intermittent | 0,327 mg/L | Sediment (Fresh water) | 12,46 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 12,46 mg/kg |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | STP | 9,6 mg/L | Fresh water | 0,1 mg/L |
| | Soil | 2,68 mg/kg | Marine water | 0,01 mg/L |
| | Intermittent | 0,1 mg/L | Sediment (Fresh water) | 13,7 mg/kg |
| | Oral | 0,02 g/kg | Sediment (Marine water) | 1,37 mg/kg |
| Toluene CAS: 108-88-3 EC: 203-625-9 | STP | 13,61 mg/L | Fresh water | 0,68 mg/L |
| | Soil | 2,89 mg/kg | Marine water | 0,68 mg/L |
| | Intermittent | 0,68 mg/L | Sediment (Fresh water) | 16,39 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 16,39 mg/kg |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | STP | 4168 mg/L | Fresh water | 19 mg/L |
| | Soil | 2,74 mg/kg | Marine water | 1,9 mg/L |
| | Intermittent | 190 mg/L | Sediment (Fresh water) | 70,2 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 7,02 mg/kg |

- CONTINUED ON NEXT PAGE -


SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)
8.2 Exposure controls:
A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-----------------------------------|-------------|---------------------|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours | CAT III | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-------------------------------|---|-------------|-------------------|--|
| Mandatory hand protection | Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm) | CAT III | EN ISO 21420:2020 | Replace the gloves at any sign of deterioration. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-------------------------------|---|------------|---------------------------------|---|
| Mandatory face protection | Panoramic glasses against splash/projections. | CAT II | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|-------------|--|---|
| Mandatory complete body protection | Antistatic and fireproof protective clothing | CAT III | EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018 | Limited protection against flames. |
| Mandatory foot protection | Safety footwear with antistatic and heat resistant properties | CAT III | EN ISO 13287:2020 EN ISO 20345:2011 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|----------------------|---|----------------------|--|
| Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 42,77 % weight

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| | |
|---------------------------|---------------------------------------|
| V.O.C. density at 20 °C: | 496,13 kg/m ³ (496,13 g/L) |
| Average carbon number: | 8,06 |
| Average molecular weight: | 107,09 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|--|
| Physical state at 20 °C: | Liquid |
| Appearance: | Fluid |
| Colour: |  Yellow |
| Odour: | Characteristic |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|-----------------------|
| Boiling point at atmospheric pressure: | 79 - 2230 °C |
| Vapour pressure at 20 °C: | 785 Pa |
| Vapour pressure at 50 °C: | 4153,65 Pa (4,15 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|-------------------------|
| Density at 20 °C: | 1160 kg/m ³ |
| Relative density at 20 °C: | Non-applicable * |
| Dynamic viscosity at 20 °C: | 917 cP |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | 20,5 mm ² /s |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Immiscible |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------|
| Flash Point: | 24 °C |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 265 °C |
| Lower flammability limit: | Not available |
| Upper flammability limit: | Not available |

Particle characteristics:

| | |
|-----------------------------|----------------|
| Median equivalent diameter: | Non-applicable |
|-----------------------------|----------------|

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|-----------------------|------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|------------------|
| Corrosive to metals: | Non-applicable * |
| Heat of combustion: | Non-applicable * |
| Aerosols-total percentage (by mass) of flammable components: | Non-applicable * |
| Other safety characteristics: | |
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Acute toxicity : Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- Corrosivity/Irritability:

C- Contact with the skin and the eyes (acute effect):

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|-----------------|-----------------|--------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | LD50 oral | 2100 mg/kg | Rat |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation | 11 mg/L (ATEI) | |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | LD50 oral | 3500 mg/kg | Rat |
| | LD50 dermal | 15354 mg/kg | Rabbit |
| | LC50 inhalation | 17,2 mg/L (4 h) | Rat |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Non-applicable | LD50 oral | >2000 mg/kg | |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | >20 mg/L | |
| Toluene CAS: 108-88-3 EC: 203-625-9 | LD50 oral | 5580 mg/kg | Rat |
| | LD50 dermal | 12124 mg/kg | Rat |
| | LC50 inhalation | 28,1 mg/L (4 h) | Rat |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | LD50 oral | >5000 mg/kg | Rat |
| | LD50 dermal | 9510 mg/kg | Rabbit |
| | LC50 inhalation | >20 mg/L | |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

| Identification | Concentration | Species | Genus |
|--|-----------------------------|---------------------|------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | LC50 > 10 - 100 mg/L (96 h) | | Fish |
| | EC50 > 10 - 100 mg/L (48 h) | | Crustacean |
| | EC50 > 10 - 100 mg/L (72 h) | | Algae |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | LC50 42,3 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 75 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 63 mg/L (3 h) | Chlorella vulgaris | Algae |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: Non-applicable | LC50 > 1 - 10 mg/L (96 h) | | Fish |
| | EC50 > 1 - 10 mg/L (48 h) | | Crustacean |
| | EC50 > 1 - 10 mg/L (72 h) | | Algae |
| Toluene CAS: 108-88-3 EC: 203-625-9 | LC50 13 mg/L (96 h) | Carassius auratus | Fish |
| | EC50 11,5 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 Non-applicable | | |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | LC50 10000 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 1919 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 Non-applicable | | |

Chronic toxicity:

| Identification | Concentration | Species | Genus |
|--|---------------------|---------------------|------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | NOEC 1,3 mg/L | Oncorhynchus mykiss | Fish |
| | NOEC 1,17 mg/L | Ceriodaphnia dubia | Crustacean |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | NOEC Non-applicable | | |
| | NOEC 0,96 mg/L | Ceriodaphnia dubia | Crustacean |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | NOEC Non-applicable | | |
| | NOEC 0,5 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | Biodegradability |
|---|-------------------------|------------------------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | BOD5 Non-applicable | Concentration Non-applicable |
| | COD Non-applicable | Period 28 days |
| | BOD5/COD Non-applicable | % Biodegradable 88 % |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | BOD5 Non-applicable | Concentration 100 mg/L |
| | COD Non-applicable | Period 14 days |
| | BOD5/COD Non-applicable | % Biodegradable 90 % |
| Toluene CAS: 108-88-3 EC: 203-625-9 | BOD5 2,5 g O2/g | Concentration 100 mg/L |
| | COD Non-applicable | Period 14 days |
| | BOD5/COD Non-applicable | % Biodegradable 100 % |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | BOD5 Non-applicable | Concentration Non-applicable |
| | COD 0 g O2/g | Period 28 days |
| | BOD5/COD Non-applicable | % Biodegradable 73 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential |
|---|---------------------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | BCF 9 |
| | Pow Log 2.77 |
| | Potential Low |

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Bioaccumulation potential | |
|---|---------------------------|----------|
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | BCF | 1 |
| | Pow Log | 3.15 |
| | Potential | Low |
| Toluene CAS: 108-88-3 EC: 203-625-9 | BCF | 90 |
| | Pow Log | 2.73 |
| | Potential | Moderate |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | BCF | 1 |
| | Pow Log | -0.06 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|--|-----------------------|----------------------|------------|-------------------------------|
| Xylene CAS: 1330-20-7 EC: 215-535-7 | Koc | 202 | Henry | 524,86 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | Non-applicable | Moist soil | Yes |
| Ethylbenzene CAS: 100-41-4 EC: 202-849-4 | Koc | 520 | Henry | 798,44 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2,859E-2 N/m (25 °C) | Moist soil | Yes |
| Toluene CAS: 108-88-3 EC: 203-625-9 | Koc | 178 | Henry | 672,8 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | 2,793E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 163, 367, 650
 Tunnel restriction code: D/E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Marine pollutant: No
14.6 Special precautions for user
 Special regulations: 223, 955, 163, 367
 EmS Codes: F-E, S-E
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
 Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- 14.1 UN number or ID number:** UN1263
14.2 UN proper shipping name: PAINT
14.3 Transport hazard class(es): 3
 Labels: 3
14.4 Packing group: III
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
 Article 95, REGULATION (EU) No 528/2012: Non-applicable

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Laboral exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2022/431, of the European Parliament and of the Council, of March 9, 2022, amending Directive 2004/37/EC, relating to the protection of workers against risks related to exposure to carcinogens or mutagens during work.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION **

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
 - Barium Sulfate (7727-43-7)
 - Cobalt bis(2-ethylhexanoate) (136-52-7)
 - 2-ethylhexanoic acid, zirconium salt (22464-99-9)

Substances that contribute to the classification (SECTION 2):

- Removed substances
 - Ethylbenzene (100-41-4)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements
- Precautionary statements
- Supplementary information

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H335: May cause respiratory irritation.

H412: Harmful to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H226: Flammable liquid and vapour.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION ** (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Skin Irrit. 2: Calculation method

STOT SE 3: Calculation method

Aquatic Chronic 3: Calculation method

STOT RE 2: Calculation method

Flam. Liq. 3: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

**** Changes with regards to the previous version**

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -