



## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** ACRYL 172  
**Other means of identification:**  
**UFI:** Q5E2-PP76-C00F-Q22A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Industrial paint. For professional users/industrial user only.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
Roberlo S.A.U.  
Ctra. Nacional II, Km. 706,5  
17457 Riudellots de la Selva - Gerona - España  
Phone: +34 972 478060 (8:00-12:45 / 14:15-17:30 h) (GMT +1:00) - Fax: +34972477394  
msds@roberlo.com
- 1.4 Emergency telephone number:** +44 (0)1924 431679 / 112 / +34 972 478060 (8:00-12:45 / 14:15-17:30 h) ROBERLO (Spain) (GMT + 1:00)

## SECTION 2: HAZARDS IDENTIFICATION \*\*

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Danger**
- 
- Hazard statements:**  
H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.  
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking.
- Substances that contribute to the classification**  
Butanone; propan-2-ol; Ethyl acetate; N-butyl acetate
- UFI:** Q5E2-PP76-C00F-Q22A
- 2.3 Other hazards:**  
Product does not meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product does not meet the criteria.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -


**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\***
**3.1 Substance:**

Non-applicable

**3.2 Mixture:**
**Chemical description:** Mixture composed of additives and resins in solvents

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 78-93-3 EC: 201-159-0 Index: 606-002-00-3 REACH: 01-2119457290-43-XXXX	<b>Butanone<sup>(1)</sup></b> ATP CLP00		<b>25 - &lt;50 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 67-63-0 EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25-XXXX	<b>propan-2-ol<sup>(1)</sup></b> ATP CLP00		<b>10 - &lt;25 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	
CAS: 141-78-6 EC: 205-500-4 Index: 607-022-00-5 REACH: 01-2119475103-46-XXXX	<b>Ethyl acetate<sup>(1)</sup></b> ATP CLP00		<b>10 - &lt;25 %</b>
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 112-07-2 EC: 203-933-3 Index: 607-038-00-2 REACH: 01-2119475112-47-XXXX	<b>2-butoxyethyl acetate<sup>(1)</sup></b> ATP CLP00		<b>5 - &lt;10 %</b>
	Regulation 1272/2008	Acute Tox. 4: H312+H332 - Warning	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	<b>N-butyl acetate<sup>(1)</sup></b> ATP CLP00		<b>2,5 - &lt;5 %</b>
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

**SECTION 4: FIRST AID MEASURES**
**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

In case of consumption, seek immediate medical assistance showing the SDS for the product.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

- CONTINUED ON NEXT PAGE -



## SECTION 4: FIRST AID MEASURES (continued)

### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media:

#### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

#### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

#### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

#### A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

#### B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -



## SECTION 7: HANDLING AND STORAGE (continued)

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
Butanone CAS: 78-93-3 EC: 201-159-0		IOELV (8h)	200 ppm	600 mg/m <sup>3</sup>
		IOELV (STEL)	300 ppm	900 mg/m <sup>3</sup>
Ethyl acetate CAS: 141-78-6 EC: 205-500-4		IOELV (8h)	200 ppm	734 mg/m <sup>3</sup>
		IOELV (STEL)	400 ppm	1468 mg/m <sup>3</sup>
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3		IOELV (8h)	20 ppm	133 mg/m <sup>3</sup>
		IOELV (STEL)	50 ppm	333 mg/m <sup>3</sup>
N-butyl acetate CAS: 123-86-4 EC: 204-658-1		IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>
		IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>

### DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m <sup>3</sup>	Non-applicable
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	500 mg/m <sup>3</sup>	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable
	Inhalation	1468 mg/m <sup>3</sup>	1468 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	120 mg/kg	Non-applicable	169 mg/kg	Non-applicable
	Inhalation	Non-applicable	333 mg/m <sup>3</sup>	133 mg/m <sup>3</sup>	Non-applicable

- CONTINUED ON NEXT PAGE -



## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	600 mg/m <sup>3</sup>	600 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>

### DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m <sup>3</sup>	Non-applicable
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	89 mg/m <sup>3</sup>	Non-applicable
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable
	Inhalation	734 mg/m <sup>3</sup>	734 mg/m <sup>3</sup>	367 mg/m <sup>3</sup>	367 mg/m <sup>3</sup>
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	Oral	36 mg/kg	Non-applicable	8,6 mg/kg	Non-applicable
	Dermal	72 mg/kg	Non-applicable	102 mg/kg	Non-applicable
	Inhalation	Non-applicable	200 mg/m <sup>3</sup>	80 mg/m <sup>3</sup>	Non-applicable
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
	Inhalation	300 mg/m <sup>3</sup>	300 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>	35,7 mg/m <sup>3</sup>

### PNEC:

Identification					
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55,8 mg/L	
	Soil	22,5 mg/kg	Marine water	55,8 mg/L	
	Intermittent	55,8 mg/L	Sediment (Fresh water)	284,74 mg/kg	
	Oral	1 g/kg	Sediment (Marine water)	284,7 mg/kg	
propan-2-ol CAS: 67-63-0 EC: 200-661-7	STP	2251 mg/L	Fresh water	140,9 mg/L	
	Soil	28 mg/kg	Marine water	140,9 mg/L	
	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg	
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	STP	650 mg/L	Fresh water	0,24 mg/L	
	Soil	0,148 mg/kg	Marine water	0,024 mg/L	
	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg	
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg	
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	STP	90 mg/L	Fresh water	0,304 mg/L	
	Soil	0,415 mg/kg	Marine water	0,03 mg/L	
	Intermittent	0,56 mg/L	Sediment (Fresh water)	2,03 mg/kg	
	Oral	0,06 g/kg	Sediment (Marine water)	0,203 mg/kg	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,09 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,098 mg/kg	

### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	 CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

**C.- Specific protection for the hands**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	 CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	 CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

**E.- Body protection**

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	 CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	 CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

**F.- Additional emergency measures**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	75,7 % weight
V.O.C. density at 20 °C:	691,13 kg/m <sup>3</sup> (691,13 g/L)
Average carbon number:	4,33
Average molecular weight:	84,29 g/mol

**\*\* Changes with regards to the previous version**

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES \*\*

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

#### Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	 Yellow
Odour:	Characteristic
Odour threshold:	Non-applicable *

#### Volatility:

Boiling point at atmospheric pressure:	77 - 192 °C
Vapour pressure at 20 °C:	7541 Pa
Vapour pressure at 50 °C:	30091,19 Pa (30,09 kPa)
Evaporation rate at 20 °C:	Non-applicable *

#### Product description:

Density at 20 °C:	913 kg/m <sup>3</sup>
Relative density at 20 °C:	0,915
Dynamic viscosity at 20 °C:	444 cP
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Immiscible
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

#### Flammability:

Flash Point:	12 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	300 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

#### Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

### 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

#### Other safety characteristics:

\*Not relevant due to the nature of the product, not providing information property of its hazards.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES \*\* (continued)

Surface tension at 20 °C: Non-applicable \*

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

\*\* Changes with regards to the previous version

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION \*\*

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

#### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

#### B- Inhalation (acute effect):

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Corrosivity/Irritability:

#### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

#### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

### H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1480 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (4 h)	Rat
propan-2-ol CAS: 67-63-0 EC: 200-661-7	LD50 oral	5280 mg/kg	Rat
	LD50 dermal	12800 mg/kg	Rat
	LC50 inhalation	72,6 mg/L (4 h)	Rat
Butanone CAS: 78-93-3 EC: 201-159-0	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23,5 mg/L (4 h)	Rat
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation	23,4 mg/L (4 h)	Rat
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	

### 11.2 Information on other hazards:

#### Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

#### Other information

Non-applicable

\*\* Changes with regards to the previous version

## SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

### 12.1 Toxicity:

#### Acute toxicity:

Identification	Concentration	Species	Genus
Butanone CAS: 78-93-3 EC: 201-159-0	LC50 3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50 5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
propan-2-ol CAS: 67-63-0 EC: 200-661-7	LC50 9640 mg/L (96 h)	Pimephales promelas	Fish
	EC50 13299 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	LC50 230 mg/L (96 h)	Pimephales promelas	Fish
	EC50 717 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 3300 mg/L (48 h)	Scenedesmus subspicatus	Algae
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	LC50 80 mg/L (48 h)	Leuciscus idus	Fish
	EC50 37 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 500 mg/L (72 h)	Scenedesmus subspicatus	Algae
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50 Non-applicable		
	EC50 Non-applicable		
	EC50 675 mg/L (72 h)	Scenedesmus subspicatus	Algae

#### Chronic toxicity:

Identification	Concentration	Species	Genus
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	NOEC 9,65 mg/L	Pimephales promelas	Fish
	NOEC 2,4 mg/L	Daphnia magna	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC Non-applicable		
	NOEC 23,2 mg/L	Daphnia magna	Crustacean

### 12.2 Persistence and degradability:

#### Substance-specific information:

Identification	Degradability	Biodegradability
Butanone CAS: 78-93-3 EC: 201-159-0	BOD5 2,03 g O2/g	Concentration Non-applicable
	COD 2,31 g O2/g	Period 20 days
	BOD5/COD 0,88	% Biodegradable 89 %
propan-2-ol CAS: 67-63-0 EC: 200-661-7	BOD5 1,19 g O2/g	Concentration 100 mg/L
	COD 2,23 g O2/g	Period 14 days
	BOD5/COD 0,53	% Biodegradable 86 %
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BOD5 1,36 g O2/g	Concentration 100 mg/L
	COD 1,69 g O2/g	Period 14 days
	BOD5/COD 0,8	% Biodegradable 83 %
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	BOD5 Non-applicable	Concentration 30 mg/L
	COD Non-applicable	Period 28 days
	BOD5/COD Non-applicable	% Biodegradable 77,3 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5 Non-applicable	Concentration Non-applicable
	COD Non-applicable	Period 5 days
	BOD5/COD Non-applicable	% Biodegradable 84 %

### 12.3 Bioaccumulative potential:

#### Substance-specific information:

Identification	Bioaccumulation potential
Butanone CAS: 78-93-3 EC: 201-159-0	BCF 3
	Pow Log 0.29
	Potential Low
propan-2-ol CAS: 67-63-0 EC: 200-661-7	BCF 3
	Pow Log 0.05
	Potential Low

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification	Bioaccumulation potential	
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	BCF	30
	Pow Log	0.73
	Potential	Moderate
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	BCF	3
	Pow Log	1.51
	Potential	Low
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low

### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Butanone CAS: 78-93-3 EC: 201-159-0	Koc	30	Henry	5,77 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,396E-2 N/m (25 °C)	Moist soil	Yes
propan-2-ol CAS: 67-63-0 EC: 200-661-7	Koc	1.5	Henry	8,207E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes
Ethyl acetate CAS: 141-78-6 EC: 205-500-4	Koc	59	Henry	13,58 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
2-butoxyethyl acetate CAS: 112-07-2 EC: 203-933-3	Koc	Non-applicable	Henry	5,532E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Non-applicable	Dry soil	No
	Surface tension	Non-applicable	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Non-applicable

### 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

### 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

### 12.7 Other adverse effects:

Not described

\*\* Changes with regards to the previous version

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -



## SECTION 14: TRANSPORT INFORMATION

### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- |  |                     |
|--|---------------------|
| <b>14.1 UN number or ID number:</b>                                  | UN1263              |
| <b>14.2 UN proper shipping name:</b>                                 | PAINT               |
| <b>14.3 Transport hazard class(es):</b>                              | 3                   |
| Labels:  | 3                   |
| <b>14.4 Packing group:</b>   | II                  |
| <b>14.5 Environmental hazards:</b>                                   | No                  |
| <b>14.6 Special precautions for user</b>                             |                     |
| Special regulations:   | 163, 367, 640D, 650 |
| Tunnel restriction code:   | D/E                 |
| Physico-Chemical properties:   | see section 9       |
| Limited quantities:  | 5 L                 |
| <b>14.7 Maritime transport in bulk according to IMO instruments:</b> | Non-applicable      |

### Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- |  |                |
|--|----------------|
| <b>14.1 UN number or ID number:</b>                                  | UN1263         |
| <b>14.2 UN proper shipping name:</b>                                 | PAINT          |
| <b>14.3 Transport hazard class(es):</b>                              | 3              |
| Labels:  | 3              |
| <b>14.4 Packing group:</b>   | II             |
| <b>14.5 Marine pollutant:</b>  | No             |
| <b>14.6 Special precautions for user</b>                             |                |
| Special regulations:   | 367, 163       |
| EmS Codes:   | F-E, S-E       |
| Physico-Chemical properties:   | see section 9  |
| Limited quantities:  | 5 L            |
| Segregation group:   | Non-applicable |
| <b>14.7 Maritime transport in bulk according to IMO instruments:</b> | Non-applicable |

### Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:



- |  |                |
|--|----------------|
| <b>14.1 UN number or ID number:</b>                                  | UN1263         |
| <b>14.2 UN proper shipping name:</b>                                 | PAINT          |
| <b>14.3 Transport hazard class(es):</b>                              | 3              |
| Labels:  | 3              |
| <b>14.4 Packing group:</b>   | II             |
| <b>14.5 Environmental hazards:</b>                                   | No             |
| <b>14.6 Special precautions for user</b>                             |                |
| Physico-Chemical properties:   | see section 9  |
| <b>14.7 Maritime transport in bulk according to IMO instruments:</b> | Non-applicable |

## SECTION 15: REGULATORY INFORMATION \*\*

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



## SECTION 15: REGULATORY INFORMATION \*\* (continued)

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: propan-2-ol (Product-type 1, 2, 4)  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

*\*\* Changes with regards to the previous version*

## SECTION 16: OTHER INFORMATION \*\*

### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances  
Ethyl acetate (141-78-6)
- Removed substances  
Toluene (108-88-3)

Substances that contribute to the classification (SECTION 2):

- New declared substances  
Ethyl acetate (141-78-6)
- Removed substances  
Toluene (108-88-3)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements
- Precautionary statements
- Supplementary information

Information on basic physical and chemical properties (SECTION 9):

- Flash Point

REGULATORY INFORMATION (SECTION 15):

- Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....)

### Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.  
H336: May cause drowsiness or dizziness.  
H225: Highly flammable liquid and vapour.

### Texts of the legislative phrases mentioned in section 3:

*\*\* Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -



## SECTION 16: OTHER INFORMATION \*\* (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

STOT SE 3: H336 - May cause drowsiness or dizziness.

### Classification procedure:

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

*\*\* Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -