

Ultra Clean Additive

Antigraffiti Additive for PU

DESCRIPTION AND PROPERTIES

- Antigraffiti additive for PU.
- It gives to the paint film an effective Antigraffiti effect and great ease of cleaning.
- It greatly increases the sliding power of the surface.

CHARACTERISTICS OF Ultra Clean Additive

Form of supply	Liquid
Color	Transparent
Specific weight	1,0 kg/l at 20°C
VOC content	792 g/L


SUBSTRATE AND PREPARATION OF THE SURFACE

	CLEANING	SANDING	FINAL CLEANING
Old paints	DA93	P360/400	DA93
Plastic parts	--	--	--
Steel	--	--	--
Galvanised steel	--	--	--
Aluminium	--	--	--
PRIMERS			
Primanyl 5011	DA93	---	---
Primapox 6021	DA93	Optional (P320)	DA93
Primapur 9051	DA93	Optional (P320)	DA93

For other kind of substrates consult the Technical Service (SAT).

APPLICATION

	SMALL SURFACE		LARGE SURFACE	
T(°C)	Hardener	Thinner	Hardener	Thinner
18-25	E9005/E9006	SOLV UNIVERSAL 5	E9005	SOLV UNIVERSAL 5
>25	E9005	SOLV UNIVERSAL 5	E9005/E9003	SOLV UNIVERSAL 3

	Mixing ratio Color + Ultra Clean Additive (in weight)	100: 5-12
---	---	-----------

QUALITY	COLOUR + BINDER	ULTRA CLEAN ADDITIVE	HARDENER	MIXING RATIO IN VOLUME (ON PAINT+ADDITIVE)
PUR 800-G	100	5-12%	E-9005	3:1
ACRY-PUR 900-G	100	5-12%	E-9005	3:1
ACRY-PUR 901-G	100	5-12%	E-9005	3:1
ACRY-PUR 902-G	100	5-12%	E-9005	1,5:1
ACRY-PUR 904-G	100	5-12%	E-9005	2:1
ACRY-PUR 906-G	100	5-12%	E-9005	3:1

It is necessary to take into account the addition of the Ultra Clean Additive and take off application thinner.

REMARKS

- It is necessary to take into account the addition of the Ultra Clean Additive and take off application thinner.
 - It is recommended to mix well to incorporate the Ultra Clean Additive.
 - The Ultra Clean Additive is incorporated into the polymer network so that its effect lasts over time. It is for this reason that one begins to observe the antigraffiti and sliding ability once the film has sufficiently cured.
 - If you want to recoat a surface that contains a finish with the Ultra Clean Additive, it is very important to sand it and degrease it correctly to have adhesion between layers.

SAFETY

- Check the product label.
- For more information check the Safety Data Sheets.
- Compliance with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

- Store the product in a ventilated place far from direct exposure to sunlight.
- Keep between +5°C and +30°C.

GUARANTEE

- One year in unopened original packaging.

These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. ROBERLO S.A.U declines any liability due to the incorrect use of any product.

The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. ROBERLO reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.

All clauses contained herein apply to any future changes or modifications.

For any additional technical information please consult with our Customer Service or our Technical Department.