

DAE 035/060/100/120/180/260 – Finixa masking film

Description

Rolls of plastic tape incorporated.

Approx. length (roll): 25 meters

Approx. width (meters): 25cm / 60cm / 100cm / 120cm / 180cm / 260cm

Product data

Support:	Electrostatic treatment on both sides
Material type:	HDPE High Density Polysthylene Plastic
Colour:	Natural transparent
Thickness:	8 – 9 µm
Resistance:	80°C (1h.) in cabin
Presentation:	Folded two or four times
Support tube:	Recyclable paper
Car tape:	Masking Tape 80°
UV resistance:	Max 2 days

Application

Masking tape suitable for wall-painting on building and construction sites, industrial and car repair applications when temperature does not exceed 80°C.

Features

Finixa masking film

Benefits

Pre-cut, static masking film with tape - to be torn by hand!
Heat resistant up to 80°C (1 hour).
Film is treated for optimum paint absorption.
To be unfolded by right-handed people.

Emballage:

A roll in a protective plastic bag, inside a recyclable cardboard box.

Storage and shelf life

Clean and dry in a well ventilated area, preferably at a temperature 23°C, out of direct sunlight, 50% relative humidity. Shelf life: 1,5 years.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the tapes suitability for their own applications.